



Stroke Length	▲ 50-5080 mm (2-200 in.)
---------------	--------------------------

- NOTES:
- ▲ TWO MOUNTING FEET INCLUDED WITH SENSOR FOR STROKE LENGTHS UP TO 1250mm. ONE ADDITIONAL FOOT IS INCLUDED FOR EVERY ADDITIONAL 500mm OF STROKE LENGTH.
 - ▲ MUST BE ORDERED SEPARATELY.
 - 3. TOLERANCES FOR DIMENSIONS SHOWN IN 1 DECIMAL PLACE MILLIMETERS MAY VARY UP TO ±0.3mm.
 - ▲ MAGNET SELECTED IS INCLUDED WITH PROFILE STYLE (MODEL RP) SENSOR.
 - ▲ STROKE LENGTH RANGE FOR DEVICENET OUTPUT IS 50-4780 mm (2-188 in.).

B	LOD 488 MOVED STROKE DIM. LINE TO END OF END PLATE & REMOVED SCREWS ON END PLATE	LAD	3/28/08
A	LOD 400 CREATE DRAWING	KKC	11/29/04
REV	ED / DESCRIPTION	BY	DATE
PROPRIETARY DATA UNLESS OTHERWISE SPECIFIED TOLERANCES 0 DEC. PL 1 DEC. PL ANGLES MM MM ° ' '' ±0.5 ±0.1 ±1		TITLE Install, Profile Style R-Series Position Sensor	
THE INFORMATION AND DESIGN(S) DISCLOSED HEREIN ARE THE PROPERTY OF MTS SYSTEMS CORPORATION AND MAY NOT BE USED, REPRODUCED OR DISCLOSED IN ANY FORM EXCEPT AS GRANTED IN WRITING BY MTS SYSTEMS CORPORATION. THIS RESTRICTION INCLUDES INFORMATION THAT IS IN THE PUBLIC DOMAIN OR HAS LEGITIMATELY IN THE PAST POSSESSION OF THE RECIPIENT.		MTS SYSTEMS CORPORATION SENSORS DIVISION 3001 SHELDON DRIVE, CARY NC 27513	
SIZE	D	DWG NO.	551016
PRODUCT LINE	R-Series	ISO DRAWING	REV B
SCALE	MTS	SHEET 1 OF 1	